

TRANSLINK

RANGER C – SERIES

C-180 C-220 C-225 C-235



Factory Maintenance



Street Lighting

CONTROL WITH PRECISION AND SAFETY

- Fully hydraulic controls
- Dual Controls at ground and cage
- Entry into the cage from the ground
- Safety Link Boom System
- Near Vertical Operation
- Single Lever Control for raising 2 booms
- Steel or Insulated Glass fibre cage
- Huge payload
- Rugged and stable
- Clever Boom design allows low travel height
- Mounts on all makes of truck
- Full range of options including custom line and civil defence bodies
- Meets and exceeds UK and European Standards



Up and over obstacles

SAFE SWIFT & SURE

RANGER C – SERIES

C-180 C-220 C-225 C-235



Special Applications- Custom Bodies

Options : Consult factory on all options

- ◆ Amplifier Intercom
- ◆ 110V @ cage; engine start/stop in cage
- ◆ Jack warning lights
- ◆ Line & custom bodies, crew cabs,
- ◆ Diesel Standby engine (Petrol standard)
- ◆ Full spares kit 1, 3 or 5 years operation
- ◆ Additional options available on request
- ◆ Mount at Destination package (export only)

Standard Features :

- ◆ Heavy duty construction
- ◆ Dual levelling steel cables for double safety
- ◆ 4 telescopic jacks with integral lockvalves
- ◆ Full cylinder cushioning at stroke end
- ◆ Cage lifting eye
- ◆ Painted Golden Yellow
- ◆ 360 degrees continuous rotation
- ◆ Mounted with decking, pump and PTO

Typical Applications

Road and motorway lighting; all types of building, construction, maintenance and inspection work; overhead cable; entertainment and shopping centres; façade and advertising sign work; tree trimming, television radio and communication relay stations, aircraft hangar and tailplane inspection, high rise work of all kinds

SPECIFICATIONS

RANGER Model Code	C-180	C-220	C-225	C-235
Working height	18.0m	22.0m	22.5m	23.5m
Platform height	16.0m	20.0m	20.5m	21.5m
Maximum outreach	9.5m	10.5m	11.15m	121.79m
Maximum safe working load	465kg	500kg	350kg	440kg
Cage Lifting Eye	465kg	500kg	350kg	440kg
GVW minimum	11.0 tonne	15.3 tonne	15.3 tonne	15.3 tonne
Stabiliser spread	3.05m	4.20m	4.20m	4.20m
TYPICAL OVERALL TRAVELLING DIMENSIONS				
Length	9,150mm	11,000mm	11,660mm	11,690mm
Width	2,500mm	2,500mm	2,500mm	2,500mm
Height (subject to truck details)	3,500mm	3,500mm	3,520mm	3,500mm

TRANSLINK International Sales Ltd.,

The Pigpen, Mill Farm, Farlow, Kidderminster, Worcestershire, DY14 0LP. UK

Tel : +44 (0)1746 718 740 Fax : +44 (0) 1746 718 540

E-mail: translink-international@dial.pipex.com - www.translink-international.com